

	AKTEX code	Standard		Voltage	Ah (20Hr)	CCA		Dry (D)/ Filled (F)
		Type	Code			DIN (JIS)	EN	
 <b>NEW</b>	SLJ-045A-0/1	JIS	55B24	12	45	(440)	350	D
 <b>NEW</b>	SLJ-060A-0/1	JIS	55D23	12	60	(540)	430	D
 <b>NEW</b>	SLJ-050A-0/1	JIS	48D26	12	50	(510)	390	D
	SLJ-060B-0/1	JIS	55D26	12	60	(540)	430	D
	SLJ-070A-0/1	JIS	75D26	12	70	(640)	530	D
 <b>NEW</b>	SLJ-080A-0/1	JIS	95D31	12	80	(730)	620	D
	SLE-055A-0/1	EN	55 518	12	55	255	420	D
	SLE-060A-0/1	EN	56 018	12	60	265	450	D
	SLE-062A-0/1	EN	56 218	12	62	280	480	D
	SLE-064A-0/1	EN	56 418	12	64	300	510	D
	SLE-066A-0/1	EN	56 623	12	66	320	540	D
	SLE-070A-0/1	EN	57 023	12	70	320	540	D
	SLE-072A-0/1	EN	57 223	12	72	340	570	D
	SLE-074A-0/1	EN	57 423	12	74	340	570	D
	SLE-090A-0/1	EN	59 030	12	90	430	720	D
	SLE-100A-0/1	EN	60 030	12	100	430	720	D
	SLE-110A-4	EN	61 030	12	110	450	760	D
	SLE-120A-4	EN	62 030	12	120	450	760	D
	SLE-130A-4	EN	63 030	12	130	450	760	D
	SLE-140A-4	EN	64 030	12	140	470	800	D
	SLE-150A-4	EN	65 035	12	150	530	850	D
	SLE-180A-4	EN	68 035	12	180	570	950	D
	SLE-190A-4	EN	69 035	12	190	705	1100	D
	SLE-200A-4	EN	70 035	12	200	730	1250	D
	SLG-140A-4*	GOST	6CT-140TM	12	140	470	800	D
	SLG-190A-4*	GOST	6CT-190TM	12	190	570	950	D

\*bakelite battery \*\* see page 31

	Dimensions, mm				Terminal type**	Terminals layout**	Ventilation system	Magic eye	Max. weight (kg)
	Length	Width	Height	T. height					
238	129	203	227	B	0 / 1	Caps	Yes	10,4	
232	173	204	225	A	0 / 1	Caps	Yes	13,2	
260	173	204	225	A	0 / 1	Caps	Yes	12,5	
260	173	204	225	A	0 / 1	Caps	Yes	13,8	
260	173	204	225	A	0 / 1	Caps	Yes	15,0	
306	173	204	225	A	0 / 1	Caps	Yes	18,3	
242	175	190	190	A	0 / 1	Caps	No	12,7	
242	175	190	190	A	0 / 1	Caps	No	13,0	
242	175	190	190	A	0 / 1	Caps	No	13,5	
242	175	190	190	A	0 / 1	Caps	No	14,0	
278	175	190	190	A	0 / 1	Caps	No	14,0	
278	175	190	190	A	0 / 1	Caps	No	14,5	
278	175	190	190	A	0 / 1	Caps	No	14,5	
278	175	190	190	A	0 / 1	Caps	No	15,0	
278	175	190	190	A	0 / 1	Caps	No	16,0	
352	175	190	190	A	0 / 1	Central	No	18,5	
352	175	190	190	A	0 / 1	Central	No	19,5	
514	175	210	210	A	4	Central	No	24,5	
514	175	210	210	A	4	Central	No	26,5	
514	175	210	210	A	4	Central	No	29,0	
514	175	210	210	A	4	Central	No	26,5	
514	218	210	217	UN (Bolt+A)	4	Central	No	30,0	
514	218	210	217	UN (Bolt+A)	4	Central	No	36,5	
514	218	210	217	UN (Bolt+A)	4	Central	No	40,0	
514	218	210	217	UN (Bolt+A)	4	Central	No	40,0	
589	238	238	238	BT	4	Caps	No	38,0	
589	238	238	238	BT	4	Caps	No	45,0	