

	AKTEX code	Standard		Voltage	Ah (20Hr)	CCA		Dry (D)/ Filled (F)
		Type	Code			DIN	EN	
	DOE-055A-0/1	EN	55 518	12	55	265	450	F
	DOE-060A-0/1	EN	56 018	12	60	280	480	F
	DOE-062A-0/1	EN	56 218	12	62	300	510	F
	DOE-066A-0/1	EN	56 623	12	66	340	570	F
	DOE-070A-0/1	EN	57 023	12	70	340	570	F
	DOE-072A-0/1	EN	57 223	12	72	360	600	F
	DOE-074A-0/1	EN	57 423	12	74	360	600	F
	DOE-077A-0/1	EN	57 723	12	77	380	640	F
	DOE-085A-0/1	EN	58 530	12	85	430	720	F
	DOE-090A-0/1	EN	59 030	12	90	450	760	F
	DOE-100A-0/1	EN	60 030	12	100	460	770	F

\*\* see page 31

	Dimensions, mm				Terminal type**	Terminals layout**	Ventilation system	Magic eye	Max. weight (kg)
	Length	Width	Height	T. height					
	242	175	190	190	A	0 / 1	Duplex	Yes	15,7
	242	175	190	190	A	0 / 1	Duplex	Yes	16,9
	242	175	190	190	A	0 / 1	Duplex	Yes	17,5
	278	175	190	190	A	0 / 1	Duplex	Yes	20,5
	278	175	190	190	A	0 / 1	Duplex	Yes	21,2
	278	175	190	190	A	0 / 1	Duplex	Yes	21,2
	278	175	190	190	A	0 / 1	Duplex	Yes	21,2
	278	175	190	190	A	0 / 1	Duplex	Yes	21,2
	352	175	190	190	A	0 / 1	Duplex	No	24,0
	352	175	190	190	A	0 / 1	Duplex	No	24,5
	352	175	190	190	A	0 / 1	Duplex	No	25,5